

FLAT ROOFLIGHT STOCK RANGE

FLAT ROOFLIGHTS



Features

- Pre-glazed for easy installation.
- Internal plasterboard pocket for easy boarding and plastering.
- Clip-in external weather bar and over trim to hide fixings.
- Weather resistant – factory sealed for longer life, recommended 5° pitched, pitched kerb allowing the water to drain off the glazing unit onto the flat roof.



Benefits

- Narrow internal sightlines for a perfect finish and a minimalistic look
- Glass U Value 1.0w/m2K
- Marine grade specification
- Standard toughened double glazed spec – 6mm/16mm gas/6mm Low-e
- Wide choice of colours - white, grey, black or dual colours - grey on white or black on white (25 year coating guarantee)



BESPOKE SIZES
Available up to
1400 x 2000 and
1000 x 3000 on
longer lead times

FLAT ROOFLIGHT

Design Code	External Kerb Size †	Sale Price excl. VAT
F1	1000 x 1000	
F2	1000 x 1500	
F3	1000 x 2000	




Pre-glazed – Clear, Neutral solar self clean, Blue Solar self clean
with Ug value 1.0W/m2k

*5 working days plus next delivery day.

† Recommended kerb width 80mm

All dimensions are external kerb dimensions

FLAT ROOF EXTERNAL KERB STOCK SIZES



Please allow an additional 5–7 days for delivery of Cool-Lite.

COOL-LITE®

Standard DGU 6/16/6mm – 90% Argon	Ug-Value [W/m2K]	Solar Factor (g-value) [%]	Light Transmission TL [%]
COOL-LITE® SKN 175 II	1.0	35	70

**FREE
GLASS
UPGRADE
COOL-LITE
SKN 175**